



Microtubes B7K Ultra Manual

Ultra Series

[Specs](#)

[Warning](#)

[Warranty](#)

[Disclaimer](#)

[EMC / EMI](#)

Specs

Controls

Master: Whereas the Level Knob controls the output of the overdrive section the Master volume adjusts the overall volume of the unit. Ideal for fine tuning the output on clean mode. It also serves as a DI level control.

Blend: Mixes the clean input signal with the overdriven signal. The clean signal remains at unity gain while the volume of the overdriven signal is set by the Level knob, allowing for fine control of the blend ratio.

Level: Sets the volume of the overdriven signal.

Drive: Sets the amount of saturation in the overdriven signal.

Attack Switch: Sets the amount of treble content to saturate: The “Boost” setting emphasizes the treble content extra clarity and presence. The “Flat” position leaves this register untouched while the “Cut” position will reduce the amount of high frequencies being saturated.

Grunt Switch: Sets the amount of low frequency content to saturate by selecting between three different bass boost levels before the clipping stage.

Bass: +-12dB @ 100Hz

Lo Mids: +-12dB switchable 250Hz, 500Hz and 1kHz

Hi Mids: +-12dB switchable 750Hz, 1.5kHz and 3kHz

Treble: +-12dB @ 5kHz.

Technical Specifications

Input Impedance: 1M Ω

Output Impedance: 1k Ω

Current Consumption: ~120mA

Voltage: 9V DC (Center Negative)

Dimensions

Width: 125 mm / 4,92"

Length: 96 mm / 3,77"

Height: 57 mm / 2,24"

Weight: 430 g / 0,94 lb

Warning

The Microtubes B7K Ultra has a current draw of 120mA. Only use a regulated 9V DC adapter with a center-negative plug. Unregulated power supplies and/or higher voltages may result in suboptimal noise performance and even damage your unit, voiding the warranty.

Warranty

To activate the warranty, we encourage you to register your product on: <http://mypedal.darkglass.com> and enter the serial number on the back of your pedal. Please contact us via email support@darkglass.com before shipping a product to us.

Disclaimer

In the interest of continuous improvement, specifications are subject to change without notice. If you have any questions, please don't hesitate to contact us at www.darkglass.com. The manufacturer claims that the above product fulfils the requirements as set by EN55013, EN55020, EN60555-2, EN60555-3, RoHS, WEEE.

1176[®], and SSL[®] are registered trademarks of their respective companies. Names of factory modes are intended for descriptive purposes only and should not be construed as an endorsement or affiliation with the companies or products named.

EMC / EMI

This equipment has been tested and found to comply with the limits for a Class B Digital device, pursuant to part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in residential installations.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. There is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to

correct the interference by one or more of the following measures:



- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment to an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.



[PRIVACY POLICY](#)

[CAREERS](#)



DARKGLASS is a registered trademark in the U.S., number 4,616,801, owned by Darkglass Electronics Oy.

Designed by Revolve Studio